



KAPCI
COATINGS

For professional use only

Issue date:
July 2010

36

Kapci Thinners

Product description

Kapci Thinners are especially designed to suite the application viscosity of Kapci Car refinish products.

With these thinners the application viscosity can be adjusted to optimize and guarantee ideal application under all conditions.

Products	Description
Kapci 600F	Thinner Fast
Kapci 600	Thinner Normal
Kapci 601	Thinner Slow
Kapci 602	Thinner Very slow
Kapci 610	Thinner Metallic

Product Application

Products	Application
Kapci 600F Thinner Fast	- Universal thinner for: Primers, Fillers, Sealers, acrylic paints, Basecoat paints and clears. - Adjust the application viscosity at low temperatures.
Kapci 600 Thinner Normal	- Universal thinner for Kapci car refinish products: Primers, Fillers, Sealers, acrylic paints, Basecoat paints and clears. - Adjust the application viscosity at normal temperatures.
Kapci 601 Thinner	- Universal thinner for Kapci car refinish products: Fillers, Slow Sealers, acrylic paints, Basecoat paints and clears. - Adjust the application viscosity at high temperatures above 30°C.
Kapci 602 Thinner Very slow	- Universal thinner for Kapci car refinish products. - Adjust the application viscosity at high temperatures above 35°C. NOTE: Do NOT use Kapci 602 Very slow thinner in Kapci Basecoat paints.
Kapci 610 Thinner Metallic	- Thinner for Kapci Basecoat paints only.

These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets

www.kapci.com

Kapci Car
Refinishes
System

General process notes

Table below are given as guideline. For detailed information refer to TDS of the respective Kapci products.

Selection of Thinners	Kapci 600F Fast	Kapci 600 Normal	Kapci 601 Slow	Kapci 602 ¹⁾ Very slow	Kapci 610 ²⁾ Metallic
Complete car or large objects	Unsuitable	Ideal	Suitable	Suitable	Suitable
Partial repair (spot repair)	Ideal	Suitable	Suitable	Suitable	Suitable
Low temperatures from +15°C to +20°C	Ideal	Suitable	Unsuitable	Unsuitable	Suitable
Normal temperatures from +20°C to +25°C	Not particularly suitable	Ideal	Suitable	Not particularly suitable	Suitable
High Temperatures above +30°C	Unsuitable	Suitable	Ideal	Suitable	Suitable
High temperatures above +35°C	Unsuitable	Not particularly suitable	Suitable	Ideal	Suitable

- 1) Do NOT mix Kapci 602 Very slow thinner with Kapci Basecoat paints.
- 2) Use Kapci 610 Thinner metallic in Kapci basecoat paints only. Do NOT mix with other Kapci 2K products.

Selection of Thinners	Kapci 600F Fast	Kapci 600 Normal	Kapci 601 Slow	Kapci 602 Very slow	Kapci 610 Metallic
Kapci 1K Etch Primer	Suitable	Ideal	Not particularly suitable	Not particularly suitable	Unsuitable
Kapci 2K Fillers	Suitable	Ideal	Suitable	Suitable	Unsuitable
Kapci 2K Sealers	Suitable	Ideal	Suitable	Suitable	Unsuitable
Kapci 2K Acrylic paints	Suitable	Ideal	Suitable	Suitable	Unsuitable
Kapci Basecoat paints	Suitable	Suitable	Suitable	Unsuitable	Suitable
Kapci 2K Clear coats	Suitable	Ideal	Suitable	Suitable	Unsuitable

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet;
2. Observe the precautionary notices displayed on the container;
3. Goggles and suitable protective equipment must be worn while using these products;
4. Good ventilation must be provided in the working environment;

This information is the result of our knowledge but given without warranty.